

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 01/18/2021 Version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: ALDOCOAT 916 One-Pass Rubber Roof Coating

Product name Product form

: Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Aldo Coatings 1320 Litton Drive Salisbury, NC 28147 (704) 932-3054

1.4. Emergency telephone number

Emergency number

: (800) 535-5053 (INFOTRAC)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	е
---	---

GHS-US classification

 Flam. Liq. 3
 H226

 Eye Irrit. 2A
 H319

 Skin Sens. 1
 H317

 Carc. 1A
 H350

 STOT SE 3
 H336

 STOT RE 1
 H372

 Asp. Tox. 1
 H304

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

Hazard statements (GHS-US)

Precautionary statements (GHS-US)

: Danger

- : H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
 - H336 May cause drowsiness or dizziness
- H350 May cause cancer
- H372 Causes damage to organs through prolonged or repeated exposure
- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, hot surfaces, open flames, sparks. No smoking P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical, lighting, ventilating equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P260+P261 Do not breathe mist, spray, vapours
- P264 Wash clothing, hands, forearms and face thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear eye protection, face protection, protective gloves, protective clothing
- P301+P310 IF SWALLOWED: Immediately call a poison center

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P308+P313 If exposed or concerned: Get medical advice/attention
- P312+P314 Get medical advice/attention if you feel unwell
- P321 Specific treatment (see first aid instructions on this label)
- P331 Do NOT induce vomiting
- P333+P337+P313 If skin or eye irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse
- P370+P378 In case of fire: Use carbon dioxide (CO2), dry sand, foam to extinguish

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool. P405 - Store locked up P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or

P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

Other hazards not contributing to the classification

: None under normal conditions.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	15 - 30
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	10 - 20
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	3 - 7
Nonane	(CAS No) 111-84-2	1 - 3
Silica: Crystalline, quartz	(CAS No) 14808-60-7	1 - 5
Ceramic materials and wares, chemicals	(CAS No) 66402-68-4	1 - 5
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS No) 41556-26-7	0.1 - 1
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	(CAS No) 82919-37-7	0.15

SECTION 4: First aid measures

4.1. Description of first aid measures

4.1. Description of mist all measures	
First-aid measures general	: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention immediately.
First-aid measures after eye contact	: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.
4.2. Most important symptoms and effe	cts, both acute and delayed
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: May cause cancer. Causes damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures		
5.1.	Extinguishing media	
Suitable	e extinguishing media	: Foam. Dry powder. Carbon dioxide.
Unsuita	ble extinguishing media	: Do not use a heavy water stream.
5.2.	5.2. Special hazards arising from the substance or mixture	
Fire haz	zard	: This product is flammable.
Explosi	on hazard	: May create vapor/air explosion hazard in confined spaces.
Reactiv	ity	: Flammable liquid and vapour.
5.3.	Advice for firefighters	
Firefigh	ting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. **SECTION 6: Accidental release measures** Personal precautions, protective equipment and emergency procedures 6.1. General measures : Remove ignition sources. Keep upwind. 6.1.1. For non-emergency personnel Protective equipment : Wear Protective equipment as described in Section 8. Emergency procedures : Evacuate unnecessary personnel. 6.1.2. For emergency responders Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency. 6.2. **Environmental precautions** Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. 6.3. Methods and material for containment and cleaning up For containment Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams Methods for cleaning up Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). 6.4. Reference to other sections No additional information available **SECTION 7: Handling and storage** 7.1. Precautions for safe handling Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety procedures. Keep container closed when not in use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Store in dry, well-ventilated area. Keep container closed when not in use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Petroleum distillates, hydrotreated light (64742-47-8)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	
Nonane (111-84-2)		
ACGIH TWA (ppm)	200 ppm	
Remark (ACGIH)	Threshold Limit Values (TLV Basis) Critical Effects - CNS Impairment	
OSHA PEL (TWA) (mg/m³)	1050 mg/m ³	
OSHA PEL (TWA) (ppm)	200 ppm	
Solvent naphtha, petroleum, light aromatic (64742-	95-6)	
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	
Silica: Crystalline, quartz (14808-60-7)		
ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)	
OSHA PEL (TWA) (mg/m³)	(30)/(%SiO2 + 2) total dust; (10)/(%SiO2 + 2) respirable fraction	
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction	
Ceramic materials and wares, chemicals (66402-68-4)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene, 1,2,4-trimethyl- (95-63-6)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (4155	6-26-7)	
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	

8.2. Exposure controls

Eye protection

Skin and body protection Respiratory protection

Appropriate engineering controls	: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.
Personal protective equipment	: Gloves. Protective goggles. Wear chemically impervious apron over labcoat and full coverage clothing. Insufficient ventilation: wear respiratory protection.
Hand protection	: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier. Change contaminated gloves immediately.

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

- : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
- : Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical	and chemical properties
Physical state	: Liquid
Color	: No data available.
Odor	: Slight hydrocarbon odor.
Odor Threshold	: No data available
рН	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 154.4 - 178.3 °C (310-353 °F)
Flash point	: 38.3 - 39.4 °C (101-103°F)
Auto-ignition temperature	: 230 °C (450°F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 2 mm Hg at 20°C (68°F)
Relative vapour density at 20 °C	: Heavier than air
Relative density	: 1.07
Solubility	: Water: Negligible
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
REVISION DATE: 01/18/2021	ALDOCOAT 916 One-Pass Rubber Roof Coating

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidising properties	: No data available
Explosive limits	: 1 - 8.9 vol %
9.2. Other information	
VOC content	: 470 g/l
SECTION 10: Stability and reactivit	zy l
10.1. Reactivity Flammable liquid and vapour.	
10.2. Chemical stability No data available.	
10.3. Possibility of hazardous reactions No data available.	3

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition. Heat. Prevent vapor accumulation.

Incompatible materials 10.5.

Strong acids. Strong alkalis. Oxidizing agents.

10.6. Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified	
Petroleum distillates, hydrotreated light (64742-47-8)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h	
Nonane (111-84-2)		
LC50 inhalation rat (ppm)	3200 ppm/4h	
Solvent naphtha, petroleum, light aro	matic (64742-95-6)	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (ppm)	3400 ppm/4h	
Silica: Crystalline, quartz (14808-60-7)		
LD50 oral rat	500 mg/kg	
ATE CLP (oral)	500.000 mg/kg bodyweight	
Benzene, 1,2,4-trimethyl- (95-63-6)		
LD50 oral rat	3280 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
ATE CLP (gases)	4500.000 ppmv/4h	
ATE CLP (vapours)	11.000 mg/l/4h	
ATE CLP (dust,mist)	1.500 mg/l/4h	
Bis(1,2,2,6,6-pentamethyl-4-piperidyl)	sebacate (41556-26-7)	
LD50 oral rat	2615 mg/kg	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified.	
Carcinogenicity	: May cause cancer.	
Cumene (98-82-8)		
IARC group	2B - Possibly carcinogenic to humans	
Silica: Crystalline, quartz (14808-60-7)	Silica: Crystalline, quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans	
Titanium dioxide (13463-67-7)		
IARC group	2B - Possibly carcinogenic to humans	

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: May cause cancer. Causes damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: Aquatic toxicity rating not determined. All possible measures should be taken to prevent release into the environment.
12.2. Persistence and degradability	
ALDOCOAT 916 One-Pass Rubber Roof Coa	iting
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
No additional information available	
SECTION 13: Disposal consideration	15
13.1. Waste treatment methods	Do not discharge to public westowater systems with sub-sample of a silving sector booth silving
Waste treatment methods	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
SECTION 14: Transport information	
In accordance with DOT	
Transport document description	: UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III
UN-No.(DOT)	: 1263
DOT NA no.	: UN1263
Proper Shipping Name (DOT)	: Paint
	including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base
Department of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
Packing group (DOT)	: III - Minor Danger
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	ů.
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
-----------------------------	---

Additional information

Other information

: No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

ALDOCOAT 916 One-Pass Rubber Roof Coating						
All chemical substances in or are exempt	n this product a	ire listed	I in the EPA (Environment Protection	Agency) TSCA (Toxic Substances Control Act) Inventory		
SARA Section 311/312 Ha	azard Classes		Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard			
	CAS #:	7440	-50-8 (Copper)			
Section 302 (EHS) TPQ				lb		
Section 304 EHS RQ				lb		
CERCLA RQ			5000	lb		
Section 313	1		Listed on SARA section 13			

	CAS #:	108-88-3 (Toluene)	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		1000) lb
Section 313		Listed on SARA section 13	}

	CAS #:	123-86-4 (n-Butyl acetate)			
Section 302 (EHS) TPQ				lb	
Section 304 EHS RQ				lb	
CERCLA RQ			5000	lb	
Section 313		N	ot Listed		

	CAS #:	50-00-0 (Formaldehyde)	
Section 302 (EHS) TPQ		500	lb
Section 304 EHS RQ		100	lb
CERCLA RQ		100	lb
Section 313		Listed on SARA section 13	

	CAS #:	7439-92-1 (Lead)	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		10	lb
Section 313		Listed on SARA section 13	

	CAS #:	7440-02-0 (Nickel)	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		100	lb
Section 313		Listed on SARA section 13	

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	CAS #:	7439-97-6 (Mercury)		
Section 302 (EHS) TPQ			lb	
Section 304 EHS RQ			lb	
CERCLA RQ		1	lb	
Section 313		Listed on SARA section 13		

	CAS #:	7440-43-9 (Cadmium)	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		10	lb
Section 313		Listed on SARA section 13	

	CAS #:	7440-38-2 (Arsenic)		
Section 302 (EHS) TPQ			lb	
Section 304 EHS RQ			lb	
CERCLA RQ		1	lb	
Section 313		Listed on SARA section 13		

	CAS #:	71-43-2 (Benzene)	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		10	lb
Section 313		Listed on SARA section 13	

	CAS #:	1330-20-7 (Xylenes)	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		100	lb
Section 313		Listed on SARA section 13	

	CAS #:	98-82-8 (Cumene)	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		5000	lb
Section 313		Listed on SARA section 13	

	CAS #:	95-63-6 (Benzene, 1,2,4-trimethyl-)	
Section 302 (EHS) TPQ		lb	
Section 304 EHS RQ		lb	
CERCLA RQ		lb	
Section 313	Listed on SARA section 13		

	CAS #:	78-83-1 (Isobutyl Alcohol)		
Section 302 (EHS) TPQ			lb	
Section 304 EHS RQ			lb	
CERCLA RQ		5000	lb	
Section 313		Not Listed		

	CAS #:	AS #: 1344-28-1 (Aluminum Oxide)		
Section 302 (EHS) TPQ		lb		
Section 304 EHS RQ		lb		
CERCLA RQ		lb		

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 313	Listed on SARA section 13		
	CAS #:	148-79-8 (Thiobendazole)	
Section 302 (EHS) TPQ		lb	
Section 304 EHS RQ	lb		
CERCLA RQ	lb		
Section 313	Listed on SARA section 13		

- - - -

15.2. International regulations

No additional information available.

15.3. US State regulations

California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Cumene (98-82-8)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Silica: Crystalline, qua	rtz (14808-60-7)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Nickel oxide (1313-99-1	1)	·		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Titanium dioxide (1346	3-67-7)		ł	ł
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Carbon black (1333-86-	-4)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Toluene (108-88-3)	1	1	1	1
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
Formaldehyde (50-00-0))	1	1	1
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

1

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene (71-43-2)		T		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity -	U.S California - Proposition 65 - Reproductive Toxicity -	No significance risk level (NSRL)
		Female	Male	
Yes	Yes	No	Yes	
Arsenic (7440-38-2)				
U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	No significance risk level (NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male	
Yes	Yes	No	No	
Cadmium (non-pyrophor	ic) (7440-43-9)			
U.S California -	U.S California -	U.S California -	U.S California -	No significance risk level
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRĹ)
Yes	Yes	No	Yes	
Mercury (7439-97-6)				
U.S California -	U.S California -	U.S California -	U.S California -	No significance risk level
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRL)
No	Yes	No	No	
Nickel (7440-02-0)				
U.S California -	U.S California -	U.S California -	U.S California -	No significance risk level
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRL)
Yes	No	No	No	
Lead (7439-92-1)				
U.S California -	U.S California -	U.S California -	U.S California -	No significance risk level
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRL)
Yes	Yes	Yes	Yes	
Nonane (111-84-2)				
U.S New Jersey - Right t U.S Massachusetts - Rig U.S Pennsylvania - RTK		List		
Silica: Crystalline, quartz	(14808-60-7)			
	o Know Hazardous Substance	List		
U.S Pennsylvania - RTK U.S Massachusetts - Rig	(Right to Know) List			
Titanium dioxide (13463-	67-7)			
U.S Massachusetts - Rig	-			
	o Know Hazardous Substance	List		
Benzene, 1,2,4-trimethyl-	(95-63-6)			
	o Know Hazardous Substance	List		
U.S Massachusetts - Rig U.S Pennsylvania - RTK	ht To Know List (Right to Know) - Environment	al Hazard List		
Carbon black (1333-86-4) U.S New Jersey - Right t	o Know Hazardous Substance	List		
Lead (7439-92-1)				
U.S New Jersey - Right t U.S Massachusetts - Rig				
U.S Pennsylvania - RTK	(Right to Know) - Environment	al Hazard List		
REVISION DATE: 01/18/2021	ALDOCOAT 9	16 One-Pass Rubber Roof Coating	g	10/11

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Copper (7440-50-8)	
U.S New Jersey - Right to Know U.S Massachusetts - Right To Kr U.S Pennsylvania - RTK (Right to	
Limestone (1317-65-3)	
U.S New Jersey - Right to Know	Hazardous Substance List
SECTION 16: Other inform	nation
Indication of changes	: Version: 2.1.
Revision date	: 01/18/2021
Other information	: Author: BP.
NFPA health hazard	2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2*
Flammability	: 2
Physical	: 0
Personal Protection	:

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product